

# Certification in a nutshell

## Discharge of rainwater, intended for siphonic systems group

The product is certified by a certification body accredited according to ISO CEI 17 065 by a body recognized by E.A. (European cooperation for Accreditation).

The certified characteristics are the following:

- Solid wall PVC discharge of rainwater, intended for siphonic systems family
- According to Standard NF EN 1329-1:
- Dimensional characteristics (diameter, thickness, out-of-roundness, sockets),
- Tensile strength,
- Impact resistance,
- Tightness under negative pressure.

The certification reference system is being developed by gathering the views of the different stakeholders:

- professionals producing the product and/or providing the service,
- consumers, users, specifiers,
- administrations, technical experts.

The certification reference system and the valid certificates (or the list of the certified products) are available to the public, free of charge and without any identification information requirement, via a website or any other means.

Whenever technically possible, the certified products are specifically marked, at least with reference to the mark.

The certified characteristics are assessed under the responsibility of the certification body, on the basis of the following checks:

	Admission	Continuous surveillance
Performance an audit of the production by a qualified technical auditor: - Supervision of controls and records of the production: raw materials, processes, end products - Supervision of the quality management provisions: metrology, packaging, storage, traceability, marking of the product, handling nonconformities and customer complaints - Supervision of tests on certified characteristics, if applicable.	Yes	Yes <b>Frequency:</b> 2 audits every 12 months *
Performing tests in a laboratory recognised by the certification body (independent and competent): - Sampling by the certification body on the production site	Yes	Yes <b>Frequency:</b> every 12 months

- (\*) - The frequency may be reduced to 1 audit every 12 months, providing that:
- + the previous assessment results have been very successful
  - The audit frequency may be raised to 2 audits every 12 months whenever critical non-conformities are being observed (depending on the relevance of the corrective actions suggested).

This data sheet is a synthesis and aims at a quick understanding by any specifier of the scope and assessment rules for the certification.

The Internet user agrees that his/her analysis and interpretation of this information and the decisions he/she will make considering this information are under his/her own responsibility. As a consequence, he/she will not seek CSTB's liability for the direct or indirect consequences of any nature that may result from the analysis and interpretation of this information, and he/she guarantees CSTB against all claims from third parties based on any damage they may suffer as a result of the analysis and interpretation of this information.