



European Technical Assessment

**ETA-19/0283
of 08/10/2019**

(English language translation, the original version is in French language)

Nom commercial
Trade name

SLIMISOL®

Famille de produit
Product family

Panneau isolant sous vide avec un cœur microporeux à base de silice amorphe protégé par un complexe barrière multicouche.

Vacuum insulation panel consisting of a micro-porous core of amorphous silica enclosed by a multi-layer film.

Titulaire
Manufacturer

ETEX France Building Performance SA
500 rue Marcel Demonque,
84915 Avignon cedex 9
France

Usine de fabrication
Manufacturing plant

SINT-NIKLAAS
(Belgique)

Cette évaluation contient :

6 pages incluant 0 annexes qui font partie intégrante de cette évaluation

This Assessment contains

6 pages including 0 annexes which form an integral part of this assessment

Base de l'ETE

Document d'Evaluation Européen (DEE) (EAD 040011-00-1201) « Panneaux d'isolation sous vide (VIP) avec enveloppe de protection, juillet 2017 »

Basis of ETA

European Technical Assessment (EAD) (EAD 040011-00-1201) "Vacuum insulation panels (VIP) with factory applied protection layers, December 2017"

Cette évaluation est :

une extension commerciale de l'ETE 13/1026 du 23/08/2019

This Assessment is

a commercial extension of ETA 13/1026 of 23/08/2019

The European Technical Assessment is issued by the Technical Assessment Body in its official language. Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and shall be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may only be made with the written consent of the issuing Technical Assessment Body. Any partial reproduction shall be identified as such.

This European Technical Assessment may be withdrawn by the issuing Technical Assessment Body, in particular pursuant to information by the Commission in accordance with Article 25(3) of Regulation (EU) No 305/2011.

SPECIFIC PART

1 Technical: definition of product and intended use

1.1 Definition of product

The insulation SLIMISOL® product is a vacuum insulation panel, consisting of a micro-porous core of amorphous silica enclosed by a multi-layer film, a barrier against water vapour and air.

1.2 Composition and manufacturing-process

The SLIMISOL® product contains:

- a core composed of amorphous silica, silicon carbide and cellulose filaments,
- a multilayer barrier film to water vapour and air, consisting of PE and PET film.

The production process uses the following raw materials: fumed silica, opacifiers, fibers, shrinkwrapping film and barrier film.

The microporous core material includes fumed silica, an opacifier and fibers. On the mixing platform all ingredients are carefully weighed and mixed. The microporous powder is then pressed into a panel of the desired thickness; afterwards the panels are sawn to the right dimensions to be used as VIP cores.

The next steps of the manufacture of VIP include shrinkwrapping of the core, drying of the core, assembly of the dried core into the barrier film, evacuation and sealing in the vacuum equipment, and finishing of the VIP as specified.

2 Specification of the intended use in accordance with the applicable European Assessment Document (EAD)

The panel is a thermal insulation for buildings.

It is used in new construction and in renovation, under normal humidity and temperature conditions within the walls in the internal part of buildings:

- insulation at the inside of walls,
- insulation of non-heating ceilings,
- insulation of flat roofs and pitched roofs (in association with another thermal insulation on the outside face),
- insulation under screed (except for floors with in-floor heating for which complementary insulation is required),
- insulation underneath the flooring (without in-floor heating).

A protection will need to be installed between the vacuum insulation panel and the interior of the building.

The vacuum insulation panel is to be installed protected from all humidity and liquid water.

English translation prepared by CSTB

NOTE: In those parts of the building in which the temperature or humidity are considerable (example: laundry rooms...) the SLIMISOL® product must not be used.

The correction factor for the influence of humidity is a provisional one in the EAD 040011-00-1201 "Vacuum insulation panels (VIP) with factory applied protection layers, December 2017"; furthermore, the applications are limited to intended uses where the temperature remains below 50°C.

The design value of the thermal conductivity shall be laid down according to relevant national provisions.

This European Technical Approval does not cover the complete or finished system of insulation. As for the application of all products insulating, the national codes of practice and regulations must be respected for design and implementation of construction systems.

The verifications and assessment methods on which this European Technical Assessment is based lead to the assumption of a working life of the thermal insulation products of at least 25 years. The indications given on the working life cannot be interpreted as a guarantee given by the producer, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works

3 Performance of the product and references to the methods used for its assessment

The identification tests and the assessment for the intended use of this product according to the Essential Requirements were carried out in compliance with the European Assessment Document EAD 040011-00-1201 for "Vacuum insulation panels (VIP) with factory applied protection layers, December 2017"

3.1 Nominal dimensions

	Length x width Dimensions (mm)	Tolerance (mm)
Nominal Minimal Length or width	≤ 1000	+1/-4
Nominal Minimal Length or width	> 1000	+1/-6
Minimum thickness (mm)	< 18	+2/-0
Thickness (mm)	$18 \leq e \leq 28$	+3/-0
Maximum thickness (mm)	> 28	+4/-0

Length and width:

Length and width are determined according to EN 822.

Thickness:

The thickness of the product is determined according to European standard EN 823

The values obtained of thickness, length and width are all included within the tolerances.

3.2 Apparent density

The density of the products is determined according to European standard EN 1602. The density of the VIP-elements (excluding plastic foil) is at least 160 kg/m³ and does not exceed 210 kg/m³.

3.3 Mass per square meter of the plastic foil

The mass per unit area of the plastic foil shall be determined with a calibrated scale with an accuracy of 0,01 g on samples at least 200mm x 200mm. The mass per unit area of the plastic foil shall be at least 108 g/m².

3.4 Tensile strength of the multilayer high barrier foil

The tensile strength of the multilayer high barrier foil shall be determined according to EN ISO 527-3. The test shall be carried before and after ageing (Annex B of the EAD 040011-00-1201). The value of the tensile strength before and after aging shall be declared.

The value of tensile strength before ageing is ≥ 80 MPa.

The value of tensile strength after ageing is ≥ 65 MPa.

3.5 Squareness

The squareness of the boards is determined according to European standard EN 824. The deviation from squareness on length and width does not exceed 5 mm/m

3.6 Flatness

The flatness S_{max} shall be determined in accordance with the methods described in to European standard EN 825.

$$S_{max} \leq 5 \text{ mm/m.}$$

3.7 Dimensional stability under specified temperature and humidity

The dimensional stability of the insulation products is determined according to European standard EN 1604. The test is carried out after conditioning at a temperature of $(70 \pm 2) ^\circ\text{C}$ and $(90 \pm 5) \%$ relative humidity for 48 h.

Each single value of length and width change of dimensions is less than $\pm 1\%$.

Each single value of thickness change of dimensions is less than $-2\% / +1 \%$.

3.8 Behaviour under compressive stress

The behaviour under compressive stress shall be determined in accordance with the methods described in EN 826. Each single value of the compressive stress at 10 % deformation is at least $\sigma_{10\%} = 180 \text{ kPa}$.

3.9 Internal pressure

The internal pressure shall be determined in a low pressure enclosure with the use of a laser sensor to determine the point of the shift of the barrier film during the pressure variation. The method is described in §2.2.15 of the EAD 040011-00-1201

Each single value of the internal pressure is less than 5 mbar.

3.10 Core thermal resistance

The thermal conductivity of the products is determined according to EN 12667. The declared value of thermal conductivity is determined according to EN 10 456

The fractile value of thermal conductivity representing at least 90 % of the production with a confidence limit of 90% is determined as following:

Thermal conductivity

Calculation of declared conductivity according to EAD

$$\lambda_D \text{ heart (just taking into account the ageing)} = (\lambda_{90/90} + \Delta\lambda_a) = 4,76 + 0,58 = 5,34 \text{ mW/m.K}$$

$$\lambda_D \text{ panel (taking into account the thermal bridge effect and ageing)} = (\lambda_{90/90} + \Delta\lambda_a) * F_{TB} = (4,76 + 0,58) * 1,10 = 5,87 \text{ mW/m.K}$$

$\lambda_{90/90}$ (mW/m.K)	$\Delta\lambda_a$ (mW/m.K)	$\lambda_D \text{ heart}$ (mW/m.K)	$\lambda_D \text{ panel}$ (mW/m.K)
4,76	0,58	5,34	5,87

Thermal Resistance of panel - R_D (taking into account the thermal bridge effect and ageing)

Calculation of thermal resistance

$$\Delta R_a = R_{90/90} - (\text{thickness} / \lambda_{\text{aged}})$$

$$R_D = \text{thickness} / \lambda_D \text{ panel (taking into account thermal bridge effect)}$$

Thickness (mm)	R _{90/90} (m ² .K/W)	ΔR_a (m ² .K/W)	R _D (m ² .K/W)
9	1.85	0.18	1.50
14	2.90	0.28	2.35
18	3.75	0.36	3.05
23	4.80	0.46	3.90
28	5.85	0.56	4.75
32	6.70	0.64	5.45
37	7.75	0.74	6.3
42	8.80	0.84	7.15
47	9.85	0.94	8.00

3.11 Reaction to fire

The reaction to fire of the product is not determined according to EN 13501-1.

Product	thickness (mm)	class
SLIMISOL	9 à 47	NPD

3.12 Behaviour under point load for boards exposed to compression loads

The behaviour under point load is determined according to EN 12430.

The point load PL (5) amounts to at least 1050 N.

3.13 Deformation under specified load and temperature

No performance determined

3.14 Water vapour resistance

Water vapour resistance is determined according to EN12572 :2014. (Condition B according to EN12086 :2013).

The nominal Sd value of multilayer high barrier foil is 4700 m, ($W = 4,19 \cdot 10^{-14}$ kg/m².s.Pa)..

3.15 Release of dangerous substances

For the sustainable use of natural resources, no performance was investigated for this product.

4 Assessment and verification of constancy of performance (AVCP) system applied, with reference to its legal base

In accordance with the European Assessment Document EAD 040007-00-1201, the applicable European legal act is: 1999/91/EC.

The system to be applied is: 3.

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited with CSTB.

The original French version is signed By

*Head of Hygro-Thermal properties of constructions unit
Direction of Envelope, Insulation and flooring
CSTB*